


Product datasheet

Specifications



APC Back-UPS Pro, 1500VA/
865W, Tower, 230V, 6x 6A Indian
outlets, AVR, LCD, User
Replaceable Battery

BR1500G-IN

Main

Main input voltage	230 V AC 1 phase
Plug standard	India 3-pin 16A
Efficiency at full load	170...294 V
Input frequency	50/60 Hz +/- 3 Hz auto-sensing
Output voltage	230 V AC 1 phase
Rated power in W	865 W
Rated power in VA	1500 VA
Output connection	4 IS 1293 India 3-pin 6A 2 IS 1293 India 3-pin 6A surge
Type of USB power supply	None
Maximum configurable power in VA	1500 VA
Maximum configurable power in W	865 W
Transfer time	6 ms typical : 10 ms maximum
UPS topology	Line interactive
Waveform type	Stepped approximation to a sinewave
Efficiency	85 % (full load) 86 % (half load)
Output frequency	50/60 Hz +/- 1 Hz sync to mains
Replacement battery	APCRBC124
	APCRBC144

Graphs

Run Time	View Runtime Graph
----------	------------------------------------

Complementary

Additional information	9Ah x 2 internal batteries
Battery type	Lead-acid internal included
Control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
UPS connectivity	USB port
Let through voltage rating	330 V
Surge energy rating	680 J

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Cable length	1.5 m
Number of cables	1
Color	Black
Height	301 mm
Width	114 mm
Depth	382 mm
Product weight	11.76 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	Yes
Mounting mode	Tower
Number of power module filled slots	0
Number of power module free slots	0
Redundant	No
Range of product	Back-UPS Pro
Product or component type	Uninterruptible power supply (UPS)

Environment

Product certification	BIS
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-15...45 °C
Storage altitude	0...15240 m
Relative humidity	0...95 %
Storage relative humidity	0...95 %
Acoustic level	45 dBA
Operating altitude	0...10000 ft

Batteries & Runtime

Battery type	Lead-acid battery
Battery graph comment	This graph is based on actual measured runtime data. All measurements were taken with new, fully charged batteries and a balanced resistive load (PF = 1.0). Actual runtimes may vary from the values of this graph. Actual runtimes are dependent on several v
Extendable runtime	0
Included battery module	0
Empty battery slot	0
Typical recharge time	7.2 h
RBC quantity	1
Battery life	2...4 year(s)
Battery charging power	30 W rated

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	38.1 cm
Package 1 Width	48.3 cm
Package 1 Length	22.9 cm
Package 1 Weight	13.19 kg
SCC14	10731304268793

Contractual warranty

Warranty (in months)	24 UPS 12 Battery
----------------------	-------------------



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	470 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	126 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	1 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	341 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	1 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Again



Repack and remanufacture

Recyclability potential, in %	62
End of life manual availability	End of Life Information
Removable battery	User replaceable
Take-back	No